


Service Manual



ORDER NO.
ARP2868

The chapter 1 of this Service Manual will not be reprinted. On your additional orders, we may supply only the chapter 2. For the chapter 1, please make copies and attach to the chapter 2 at your side if necessary.

FM/AM DIGITAL-SYNTHESIZER TUNER

F-303RDS

F-303RDS-G

THIS MANUAL IS APPLICABLE TO THE FOLLOWING MODEL(S) AND TYPE(S).

Type	Model		Power Requirement	Remarks
	F-303RDS	F-303RDS-G		
HEXK	○	○	AC 220V - 230V	AC 240V, *
HBXK	○	Not used	AC 240V,	AC 220V - 230V, *
HEWZIXK	○	Not used	AC 220V - 230V	AC 240V, *
HZIXK	Not used	○	AC 220V - 230V	AC 240V, *

* : Alter the wiring of the Power-supply block at the primary winding of Power-transformer referring to the "Line Voltage Selection" described in Service Manual.

CONTENTS

CHAPTER 1

1.1 CONNECTIONS	1-2
1.2 PANEL FACILITIES	1-3
1.3 SPECIFICATIONS	1-5
1.4 BLOCK DIAGRAM	1-6
1.5 FL INFORMATION	1-7
1.6 PCB PARTS LIST	1-8
1.7 ADJUSTMENTS	1-10
1.8 PARTS LIST FOR EXPLODED AND PACKING	1-12


CHAPTER 2

2.1 EXPLODED VIEWS AND PACKING	2-3
2.2 SCHEMATIC AND PCB CONNECTION DIAGRAMS	2-5

PIONEER ELECTRONIC CORPORATION 4-1, Meguro 1-Chome, Meguro-ku, Tokyo 153, Japan
PIONEER ELECTRONICS SERVICE INC. P.O. Box 1760, Long Beach, California 90801 U.S.A.
PIONEER ELECTRONICS OF CANADA, INC. 300 Allstate Parkway Markham, Ontario L3R 0P2 Canada
PIONEER ELECTRONIC [EUROPE] N.V. Haven 1087 Keetberglaan 1, 9120 Melsele, Belgium
PIONEER ELECTRONICS AUSTRALIA PTY. LTD. 178-184 Boundary Road, Braeside, Victoria 3195, Australia TEL: [03] 580-9911
© **PIONEER ELECTRONIC CORPORATION 1994**

O-FFN JULY 1994 Printed in Japan

1.2 PANEL FACILITIES



① POWER (STANDBY/ON) switch

This is the switch for electric power.

ON When set to ON position, power is supplied and the unit becomes operational.

STANDBY When set to STANDBY position, the main power flow is cut and the unit is no longer fully operational. A minute flow of power feeds the unit to maintain operation readiness.


NOTE:

- The memory will be backed up so long as the power cord is not unplugged.
- If the power cord is unplugged, the memory will be retained for several days.
- When not using the unit for a long period, disconnect the power cord.

② ACTIVE MODE button

Each time you press this button, the mode changes as follows:


FM:



NOTE:

The station name input mode and PTY search mode are skipped when the EON function is used for interrupt waiting.

AM:



③ EON button/indicator

If receiving a station broadcasting EON information, the radio can automatically keep track of broadcast information from other network stations.

If you specify traffic information (TA) or program type (PTY) beforehand, the frequency will change automatically when the specified broadcast begins.

The display's EON indicator lights when receiving EON information. When a specified TA or PTY broadcast is received, this indicator and EON in the display section flash.


④ MEMORY button

Use to preset stations.

This is also used for FM or AM broadcast manual station name character selection. When you want automatic tuning to programs of a particular musical type when using EON PTY, press this button while the desired type is displayed, and interrupt waiting begins.

⑤ BAND selector button

Each time you press this button, the band changes as follows:



⑥ CLASS button

Use to switch between preset memory classes 1 to 4. In each class, 10 stations can be memorized using the STATION CALL buttons, enabling a total of 40 stations to be memorized.

⑦ STATION CALL buttons

Use these buttons to preset stations and to receive the already preset stations. These are also used when performing direct access tuning.

⑧ RF ATT button

Set this button to on when receiving strong FM signals (nearby stations) to reduce sound distortion (RF ATT indicator lights). Normally, this button should be set to off. This button does not affect AM reception.

NOTE:
This button's status is preset for each station in station memory.


⑨ IF BAND button

Each time this button is pressed, the bandwidth of the IF circuit switches between "normal" and "narrow" for the FM band. Set to NARROW in case of interference from other stations. The NARROW indicator lights up. When not lit, normal filter bandwidth is selected. This button does not affect AM reception.

NOTE:
This button's status is preset for each station in station memory.

⑩ MPX (multiplex) MODE AUTO/MONO button

Mode changes as follows each time this button is pressed.



"AUTO" is not displayed.
This button does not affect AM reception.

AUTO:
Normally leave in this mode for reception. When a stereo FM broadcast is received, it will be automatically reproduced in stereo sound and the STEREO indicator lights up.

NOTE:
When the signal level is too weak for reception, sound output is automatically muted.

MONO:
MONO indicator lights up.
To receive stereo broadcasts in monaural.
If there is too much noise during stereo reception of a weak signal, you can reduce the level of noise by switching to MONO.

NOTE:
This button's status is preset for each station in station memory.


⑪ TUNING/STATION NAME - (down)/+ (up) buttons

Use for tuning. Press these buttons to change the frequency display (3-Speed Accel Tuning).
In the Manual Name input mode, PTY search mode and when selecting program types on EON PTY, these are used to select characters and program type.

⑫ DIRECT ACCESS button

When this button is pressed, the STATION CALL buttons function as ten-key number buttons for direct input of the desired reception frequency. Press again to cancel this mode.

OPERATING DISPLAY



① MEMORY indicator

② RF ATT indicator
Stays lit while RF ATT button is on.

③ NARROW indicator
Stays lit while IF BAND button is set to NARROW. When not lit, stays NORMAL.

④ RT, PS, PTY, CT indicator
One of these lights to indicate the selected display mode (selected by the ACTIVE MODE button).
Time is displayed when the CT data is received. It changes to frequency display mode if not lit.

⑤ EON - [PTY TA] indicator
When a station broadcasting EON information is received, EON- [] lights. After specifying TA or PTY, interrupt waiting begins and the TA or PTY indicator flashes.

⑥ RDS indicator

Lights when an RDS broadcast is received.

⑦ SIGNAL indicator
⑧ Frequency, character, clock time indicator

CT (Clock Time) data, band, RDS data and frequency data are displayed.

⑨ MONO indicator

Stays lit while MPX MODE AUTO/MONO button is set to MONO.

⑩ STEREO indicator

Lights up when a stereo broadcast is received (the indicator does not light when the MPX MODE AUTO/MONO button is set to MONO).

⑪ CLASS 1, 2, 3, 4 indicator

Shows the class selected by the CLASS button.
The current CLASS is displayed.

⑫ Station indicator

When STATION CALL buttons are pressed, it will show the corresponding channel number.

1.3 SPECIFICATIONS

FM Tuner Section

Frequency Range	87.5 MHz to 108 MHz
Usable Sensitivity	
NORMAL	Mono: 12.7 dBf, IHF (1.2 μ V/75 Ω)
50 dB Quieting Sensitivity	
NORMAL	Mono: 18.0 dBf, IHF (2.2 μ V/75 Ω)
	Stereo: 38.3 dBf, IHF (22.6 μ V/75 Ω)
Sensitivity (DIN)	
NORMAL	Mono: 0.9 μ V/75 Ω
	Stereo: 32 μ V/75 Ω
Signal-to-Noise Ratio	Mono: 80 dB (at 80 dBf)
	Stereo: 75 dB (at 80 dBf)
Signal-to-Noise Ratio (DIN)	Mono: 66 dB
	Stereo: 60 dB
Distortion (at 80 dBf)	
NARROW	Mono: 0.15 % (1 kHz)
	Stereo: 0.2 % (1 kHz)
Alternate Channel Selectivity	
NORMAL	70 dB (400 kHz)
NARROW	70 dB (300 kHz)
Stereo Separation	45 dB (1 kHz)
Frequency Response	± 1 dB (30 Hz to 15 kHz)
Image Response Ratio	80 dB
IF Response Ratio	90 dB
Subcarrier Product Ratio	70 dB
Antenna Input	75 Ω unbalanced

AM Tuner Section

Frequency Range	531 kHz to 1,602 kHz (Step 9 kHz)
Sensitivity (IHF, Loop antenna)	350 μ V/m
Selectivity	40 dB
Signal-to-Noise Ratio	55 dB
Antenna	Loop Antenna

Audio Section

Output (Level/Impedance)	
FM (100 % MOD)	650 mV/1.1 k Ω
AM (30 % MOD)	150 mV/1.1 k Ω

Miscellaneous

Power Requirements	AC 240 Volts ~, 50/60 Hz
Power Consumption	15 W
Dimensions	420 (W) x 75.5 (H) x 284 (D) mm
Weight (without package)	2.8 kg


Furnished Parts

FM T-type Antenna	1
AM Loop Antenna	1
Connecting Cord with Pin Plugs	1
Control Cord	1
Operating Instructions	1

NOTE:

Specifications and design are subject to possible modifications without notice, due to improvements.


1.4 BLOCK DIAGRAM



1.5 FL INFORMATION

■ **AAV1193 (V901)**

PIN LOCATION





PIN CONNECTION

[illegible][illegible]

NOTE

1) F1,F2 --- Filament	5) NC ----- No connection
2) NP ----- No pin	6) 1G~11G --- Grid
3) NX ----- No extend pin	7) 1C ----- Internal connection
4) DL ----- Datum Line	8) Pin50 and pin73 are connected inside.

GRID ASSIGNMENT



ANODE CONNECTION

[illegible]

1.6 PCB PARTS LIST

NOTES:

- Parts marked by "NSP" are generally unavailable because they are not in our Master Spare Parts List.
 - The Δ mark found on some component parts indicates the importance of the safety factor of the part. Therefore, when replacing, be sure to use parts of identical designation.
 - Parts marked by "◎" are not always kept in stock. Their delivery time may be longer than usual or they may be unavailable.
 - When ordering resistors, first convert resistance values into code form as shown in the following examples.
- Ex.1 When there are 2 effective digits (any digit apart from 0), such as 560 ohm and 47k ohm (tolerance is shown by J = 5%, and K = 10%).

560Ω	→	56 × 10 ¹	→	561	RD1/8PM	561J
47kΩ	→	47 × 10 ³	→	473	RD1/4PS	473J
0.5Ω	→	0R5			RN2H	0R5K
1Ω	→	010			RS1P	010K

Ex.2 When there are 3 effective digits (such as in high precision metal film resistors).

5.62kΩ	→	562 × 10 ¹	→	5621	RN1/4PC	5621F
--------	---	-----------------------	---	------	-------	---------	-------

Mark	No.	Description	Parts No.	Mark	Mark	No.	Description	Parts No.	Mark
------	-----	-------------	-----------	------	------	-----	-------------	-----------	------

LIST OF ASSEMBLIES

TUNER ASSEMBLY(HEXK TYPE)	AWE1289
└ TUNER ASSEMBLY	AWZ5319
└ POWER ASSEMBLY	AWZ5320
TUNER ASSEMBLY(HBXX TYPE)	AWE1290
└ TUNER ASSEMBLY	AWZ5319
└ POWER ASSEMBLY	AWZ5321
TUNER ASSEMBLY(HEWZIXK AND HZIXK TYPES)	AWE1288
└ TUNER ASSEMBLY	AWZ5317
└ POWER ASSEMBLY	AWZ5318
DISPLAY ASSEMBLY	AWP1054

TUNER ASSEMBLY

SEMICONDUCTORS

IC501	AN7470P
IC201	HA11225
IC301	LA1247
IC702	LC7073
IC401	LM7001J
IC502	NJM4558LD
IC602	NJM7812AS
IC801	PDG113A
IC701	PM4002B
IC101,IC102	TA7060AP
Q101,Q603	2SA1529
Q555,Q701	2SA933S
Q605	2SB560
Q102,Q109,Q251,Q501,Q556	2SC1740S
Q702,Q704,Q851	2SC1740S
Q402	2SC1740SLN
Q106-Q108,Q703	2SC2668
Q551-Q554	2SC3327
Q608	2SD880
Q401,Q502	2SK246
Q301	DTA124ES
Q103,Q105,Q606	DTA143ES
Q104,Q607	DTC124ES
Q604,Q801	DTC143ES
D201-D203,D301,D302	1SS252
D501,D502,D701,D801,D802	1SS252
D851	1SS252
D102-D105	1SS85

COILS AND FILTERS

D101	1SV156
D609	MTZJ27B
D803	MTZJ4.7
D610	MTZJ5.1A
D611	MTZJ6.2C
T101	ATE-063
T201	ATE1008
T202	ATE1009
F103,F104	ATF-107
F101	ATF-119
F102	ATF1024
F301	ATF1042
F501,F502	ATF1143
F251	ATF1152
L101-L103,L401,L801	LAU2R2K
L553 (HEWZIXK AND HZIXK TYPES)	LAU010K
L151	LAU470K
L551,L552 (HEWZIXK AND HZIXK TYPES)	LAU2R2K

CAPACITORS

C804	ACH1246
C703,C704	CCDCH220J50
C151,C403,C404	CCPUCH150J50
C315,C405-C407	CCPUSL470J50
C412	CEANL010M50
C251	CEANP4R7M50
C205	CEAS010M50
C312	CEAS100M50
C701	CEAS101M10
C501	CEAS101M16
C611	CEAS101M35
C605	CEAS102M25
C511	CEAS1R5M50
C803	CEAS221M10
C708,C808	CEAS2R2M50
C104,C209,C304,C311,C402	CEAS330M16
C409	CEAS330M16
C609	CEAS331M50
C512	CEAS3R3M50
C504,C716,C810,C852	CEAS470M10
C207	CEAS470M16
C614	CEAS470M25
C610	CEAS470M35
C212,C253,C313,C316	CEAS4R7M50
C510	CEASR22M50

Note: 4 serial F.E. module assy has no service part.

POWER ASSEMBLY

SEMICONDUCTORS

Q601, Q602	2SC2878
D601—D606	S5566

COIL

L601 (HEWZIXK AND HZIXK TYPES) ATF1135

TRANSFORMERS

ATT1253

CAPACITORS

△ C601	ACG1054
C603	CEAS330M25
C604	CKDYF473Z50
C617	CKDYX473M25
C602,C616	CQMA473J50

RESISTORS

R601,R603 RD1/4PM010J

Other Resistors

RD1/8PM□□□.

OTHERS

CABLE HOLDER (10P) AKT1083

DISPLAY ASSEMBLY

SEMICONDUCTORS

IC901	LC75712E
D901	1 SS252
D907	AEL1099
D902—D906	MTZJ7.5

SWITCHES AND RELAYS

S901 – S922 ASG1029

CAPACITORS

C901	CCPU SL300J50
C904—C906	CCPU SL470J50
C909	CEJA220M35
C902	CEJA221M6
C907,C908	CKD YX223M25
C910—C920	CKPU YB101K5
C903,C921	CKPU YY103M1

RESISTORS

All Resistors RD1/8PM□□□J

OTHERS

V901	FL TUBE(25×214.0)	AAV119
------	-------------------	--------

1.7 ADJUSTMENTS

1.7.1 FM TUNER ADJUSTMENTS

- Connect as shown in Fig. 2.
- Set the function to FM.

Step	Adjustment name	FM SG (1 kHz ± 75 kHz dev.)			FL display, IF BAND etc.	Location	Adjustment
		Frequency (MHz)	Modulation	Level (dBμV)			
1	IF sensitivity-UP adjustment	98	MONO	Low input level	98 MHz MONO	T101	Adjust so that the voltage between TP9 and GND becomes maximum.
2	T meter adjustment	98	MONO	60	98 MHz NARROW	T201	Adjust so that the voltage between TP1 and TP2 becomes 0±50 mV.
3	MONO distortion adjustment	98	MONO	60	98 MHz NARROW	T202	Adjust so that the distortion becomes minimum.
4	Repeat step 2 and 3 until optimum adjustment is obtained.						
5	VCO adjustment	108	OFF	60	108MHz NARROW	VR501	Adjust so that the output at TP3 becomes 76 kHz ±0.5 kHz.
6	STEREO distortion adjustment (NARROW)	89(*2)	L—ONLY	60	89 MHz NARROW	T101	Turn the core of T101 within a range of ±90° and adjust so that the distortion becomes minimum.
7	Muting level adjustment	98	MONO	15 ±5dB	98 MHz NORMAL	VR201	Adjust so that the muting is released at the input level shown on the left.
8	SK level adjustment	88	EXTERNAL *1 (RDS SG)	60	88 MHz NORMAL	VR701	Adjust so that the voltage between TP6 and GND becomes maximum.

*1 : RDS SG (AUDIO, PILOT, RDS, BK and DK : OFF, SK : ON)

*2 : Stereo modulation : Main 1 kHz L+R, ±68.25 kHz.
Pilot 19 kHz, ±6.75 kHz.

1.7.2 AM TUNER ADJUSTMENT

- Connect as shown in Fig. 2.
- Set the function to AM.

Step	Adjustment name	AM SG(400kHz, 30% modulation)		FL Display	Adjustment	
		Frequency(kHz)	Level(dBμV/m)		Location	Specifications
1	S meter adjustment	1008	100	1008 kHz	VR301	Adjust so that the voltage between TP4 and GND becomes 4.5V ±0.1 V.




Fig. 1 Adjustment Points





Fig. 2 Connection Diagram

1.8 PARTS LIST FOR EXPLODED VIEWS AND PACKING


- NOTES:
- Parts marked by "NSP" are generally unavailable because they are not in our Master Spare Parts List.
 - The Δ mark found on some component parts indicates the importance of the safety factor of the part. Therefore, when replacing, be sure to use parts of identical designation.
 - Parts marked by "⊙" are not always kept in stock. Their delivery time may be longer than usual or they may be unavailable.

Mark	No.	Description	Parts No.	Mark	No.	Description	Parts No.
	1	FRONT PANEL ASSY (F-303RDS SERIES)	AMB2506		24	STATION BUTTON(ABS) (F-303RDS SERIES)	AAD4055
	1	FRONT PANEL ASSY (F-303RDS-G SERIES)	AMB2511		24	STATION BUTTON(ABS) (F-303RDS-G SERIES)	AAD4065
	2	TUNER ASSEMBLY (HEXK AND HBXK TYPES)	AWZ5319		25	BONNET (F-303RDS SERIES)	ANE1518
	2	TUNER ASSEMBLY (HEWZIXK AND HZIXK TYPES)	AWZ5317		25	BONNET (F-303RDS-G SERIES)	ANE1519
	3	POWER ASSEMBLY (HEXK TYPE)	AWZ5320		26	EARTH SCREW (HEWZIXK AND HZIXK TYPES)	ABA1047
	3	POWER ASSEMBLY (HBXK TYPE)	AWZ5321		27	AIR CAP (HBXK TYPE ONLY)	AHG1203
	3	POWER ASSEMBLY (HEWZIXK AND HZIXK TYPES)	AWZ5318		28	OPE.INSTRUCTIONS (English/French/German/Italian/ Swedish/Dutch/Spanish/Portuguese) (HEXK TYPE)	ARE1296
	4	DISPLAY ASSEMBLY	AWP1054		28	OPE.INSTRUCTIONS (German/Italian) (HEWZIXK AND HZIXK TYPES)	ARE1322
	5	4 SERIAL F.E. MODULE ASSY	AXQ1004		28	OPE.INSTRUCTIONS (English) (HBXK TYPE)	ARB1462
Δ	6	FU1 (I=T400MA,V=250)	AEK-504		29	PLUG CORD	ADE-052
Δ	7	AC POWER CORD (HEXK, HEWZIXK AND HZIXK TYPES)	ADG1138		30	FM ANTENNA (HEXK AND HBXK TYPES)	ADH1016
Δ	7	AC POWER CORD (HBXK TYPE)	ADG1148		30	FM ANTENNA (HEWZIXK AND HZIXK TYPES)	ADH1019
Δ		FUSE (T5A/250V)	AEK1046		31	WARRANTY CARD	ARW1048
		(For HBXK type of AC POWER CORD)			32	LOOP ANTENNA	ATB1011
NSP	8	CHASSIS	ANA1122	NSP	33	CORD WITH PLUG	PDE1095
	9	INSULATOR	PNW1912		34	SIDE PAD A (HEXK, HEWZIXK AND HZIXK TYPES)	AHA2015
Δ	10	STRAIN RELIEF	AEC-882		34	SIDE PAD A (HBXK TYPE)	AHA2017
NSP	11	BARRIER	AEC1416		35	SIDE PAD B	AHA2016
NSP	12	PCB MOULD	AMR1525		36	PACKING CASE (F-303RDS/HEXK AND F-303RDS/HEWZIXK)	AHD2727
	13	ANTENNA LABEL (HEXK AND HBXK TYPES)	AAX1691		36	PACKING CASE (F-303RDS-G SERIES)	AHD2733
	13	ANTENNA LABEL (HEWZIXK AND HZIXK TYPES)	AAX1609		36	PACKING CASE (F-303RDS/HBXK)	AHD2728
	14	SCREW	ABA-298		37	PACKAGING SHEET	AHG1107
	15	SCREW (STEEL)	ABA1011				
	16	SCREW	ABA1018				
	17	BINDER	AEC-826				
	18	SCREW	BBZ26P100FMC				
	19	SCREW	VCZ30P060FMC				
	20	PANEL	AAK2466				
	21	NAME PLATE (F-303RDS SERIES)	PAM1608				
	21	NAME PLATE (F-303RDS-G SERIES)	AAM1059				
	22	POWER BUTTON (ABS) (F-303RDS SERIES)	AAD2425				
	22	POWER BUTTON (ABS) (F-303RDS-G SERIES)	AAD4066				
	23	BAND BUTTON (ABS) (F-303RDS SERIES)	AAD2502				
	23	BAND BUTTON (ABS) (F-303RDS-G SERIES)	AAD4067				

2.1 EXPLODED VIEWS AND PACKING









NOTE: Screws adjacent to ▼ mark on product are used for disassembly.








2.2 SCHEMATIC AND PCB CONNECTION DIAGRAMS


2.2.1 DISPLAY ASSEMBLY

- NOTE FOR PCB DIAGRAMS:
- 1. Part numbers in PCB diagrams match those in the schematic diagrams.
 - 2. A comparison between the main parts of PCB and schematic diagrams is shown below.


Symbol in PCB Diagrams	Symbol in Schematic Diagrams	Part Name
		Transistor
		Diode
		Capacitor (Polarized)

- 3. The transistor terminal marked with E or  shows the emitter.
- 4. The diode terminal marked with  or  shows cathode side.
- 5. The capacitor terminal marked with  or  shows negative terminal.


● This diagram is viewed from the mounted parts side.



● This diagram is viewed from the foil side.



SCH-1




SCH-1

DISPLAY ASSY

DISPLAY ASSY

SCH-1

TO TUNER ASSEMBLY (2/2) (→SCH-3)




SCH-2

● This diagram is viewed from the mounted parts side.

PCB-2

TUNER ASSEMBLY



Line Voltage Selection

- Line Voltage can be changed by the following modification:
1. Disconnect the AC power cord.
 2. Remove the cover.
 3. Change the position of the jumper-lines ① follows.



Voltage	jumper—line ① position
220V—230V	①
240V	②

NOTE: When replacing a PCB which has the primary winding circuit of Power-transformer, be sure to compare its circuit with the diagram in Service Manual. jumper-lines on the PCB may have to be removed. Forgetting this check-up will cause a serious damage.

4. Stick a line voltage label on the rear panel.

Part No.	Description
AAX-193	220V label
AAX-192	240V label

POWER ASSEMBLY




TO DISPLAY ASSEMBLY J1 TO DISPLAY ASSEMBLY J2

Q551
Q552
Q554
Q555
VR501
Q103
Q105
Q301
Q106
Q104
Q251
Q401
Q402
VR201
T202
T201
T101
IC102
Q703
Q107
Q603
Q604
IC502
Q801
Q701
VR701
Q608
IC801
Q702
IC701
Q607
Q606
Q704
IC702
Q601
Q602
Q605

● This diagram is viewed from the mounted parts side.

PCB-2



Line Voltage Selection

- Line Voltage can be changed by the following modification:
- 1. Disconnect the AC power cord.
- 2. Remove the cover.
- 3. Change the position of the jumper-lines ① follows.


Voltage	jumper—line ① position
220V—230V	①
240V	②

NOTE: When replacing a PCB which has the primary winding circuit of Power-transformer, be sure to compare its circuit with the diagram in Service Manual. jumper-lines on the PCB may have to be removed. Forgetting this check-up will cause a serious damage.

- 4. Stick a line voltage label on the rear panel.

Part No.	Description
AAX-193	220V label
AAX-192	240V label

POWER ASSEMBLY





TO DISPLAY ASSEMBLY J1 TO DISPLAY ASSEMBLY J2

- Q551 Q553
- Q851 Q552
- Q554
- Q555
- Q102
- Q556
- VR501
- IC502
- Q501
- IC501
- IC301
- VR301
- Q103
- Q105
- Q502 IC101
- Q301 Q109
- Q106
- Q104
- Q251 Q401
- Q108 IC401
- Q402
- IC201
- VR201
- T202
- T201
- IC102
- Q703 Q107
- Q603
- Q604
- IC602
- Q801
- Q701
- VR701
- Q608
- IC801
- Q702
- IC701
- Q607
- Q606 Q704
- IC702
- Q601
- Q602
- Q605

- This diagram is viewed from the foil side.

PCB-5




7




2.2.3 TUNER (2/2) AND POWER ASSEMBLIES

TUNER ASSEMBLY (AWZ5319:HEXK AND HBXK TYPES)
(2/2) (AWZ5317:HEWZIXK AND HZIXK TYPES)



SCH-3

TUNER (2/2) ASSY,
POWER ASSY



↗: FM Signal route (Lch)
↘: AM Signal route (Lch)

